

## FLEX WING PASTURE TOPPERS



**FEATURES:**

- Robust pivot points.
- Heavy duty transmission.
- Rubber shock absorbers between rotor gearboxes.
- Shear-bolt-Over run PTO protection.
- Patented Transmission System
- Hydraulic Wing Lift
- High Lift twin-cut swinging blades constructed from spring steel.
- 88mm (3 1/2") Blade overlap to eliminate striping.
- Hardened bushings on swinging blades.
- Undersole discs.
- Low Maintainance.
- Comprehensive MAJOR guarantee.

The NEW **MAJOR 12000** and **18000 Flex Wing Topper** are a three point linkage mounted machine which folds up offering a 7'6" transport width

Computer engineered to maximise efficiency, the MAJOR 1200FW and 1800FW toppers are of robust construction. CE conformity is achieved with Full PTO guarding & heavy rubber skirting preventing debris from escaping. The Wings cutting decks are raised by hydraulic control to transport position. Mowing position offers a wing flex from -15 to +25 degrees allowing the cutting unit to follow the ground contours.

Contra-rotating spring steel twin-cut swinging blades retained in hardened steel bushing & clamped by spring steel blade backs.

Undersole discs to prevent scalping



Flex wing design allows machine to follow ground contours. Patented transmission ensures power is delivered to the blades.



	Cutting Width	Transport Width	PTO Input	No. of Blades	kW HP	Weight Kg	Blade Tip Speed	Cutting Range
12000	3.65m 12'	2.3m 7'6"	540	8	50-75	610Kg	4411 m/min 14500 ft/min	12-250mm 1/2" - 10"
18000	5.5m 18'	2.3m 7'6"	540	12	75-90	1395Kg	4411 m/min 14500 ft/min	12-250mm 1/2" - 10"